

Newlook International, Inc. Easy Strip 1000™



Material Safety Data Sheet

Section 1 PRODUCT & COMPANY IDENTIFICATION

Product Name: Easy Strip 1000
Product Type: Coating Remover
Hazard Class: IRR
Company: Newlook International, Inc. 1525 S. Gladiola Street, Suite 8, Salt Lake City, Utah 84104
Emergency Phone: Newlook International, Inc. 801.886.9495
Information Phone: Newlook International, Inc. 877.763.9566 or 801.886.9495
Email: info@getnewlook.com

Section 2 COMPOSITION & INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	% WEIGHT	CAS Number	LD ₅₀ (Route, Species)	LC ₅₀ (Species)
Benzyl Alcohol	30 to <40	100-51-6	1230 mg / kg (oral, rat)	N / AV
Petroleum Distillate, Aromatic	4 to <7	64742-94-5	>2 mL / kg (skin, rat)	>590 mg / m3 / 4hr (rat)
Triethanolamine	1 to <3	102-71-6	4920 µL / kg (oral, rat)	N / AV

Section 3 HAZARDS IDENTIFICATION

Routes of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion
Target Organs: Skin, eyes, and respiratory tract
Emergency Overview: Moderate eye, skin, and respiratory irritant
Potential Health Effects: Chronic contact may lead to inflammation or dermatitis
WHMIS Symbols:



SPECIAL NOTE: MSDA data pertains to the product as dispensed from the container. Adverse health effects would not be expected under recommended conditions of use so long as prescribed safety precautions are practiced. See product bulletin for use instructions.

Section 4 FIRST AID MEASURES

Inhalation: Move exposed person to fresh air. If irritation persists, seek immediate medical attention.
Ingestion: DO NOT INDUCE VOMITING. If victim is conscious, give them plenty of water to drink. Seek medical attention immediately.
Eyes: Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower lids. Seek medical attention immediately.
Skin: Immediately flush contaminated skin with plenty of water. Seek medical attention for burns.

Section 5 FIRE & EXPLOSION HAZARD DATA

Flammability: Non-flammable under normal use conditions
Conditions: Must be heated above 100°C
Flash Point: >100°C (PMCC)
Autoignition Temperature: >400°C
Lower Explosive Limit: N / AV
Upper Explosive Limit: N / AV
Unusual Fire Explosion Hazards: Closed containers may rupture and burn when overheated.
Extinguishing Media: Water, Alcohol Foam, CO₂, Dry Chemical, Water Fog
Special Fire Fighting Procedures: Wear self-contained positive pressure breathing apparatus. Keep containers cool with water spray.
Hazardous Combustion Products: Carbon oxides and dark smoke may be created by combustion.
NFPA "Diamond" Rating: Health = 1
Flammability = 1

Reactivity = 0
Special Hazards = None

Section 6
ACCIDENTAL RELEASE MEASURES

Special Leak and Spill Procedures: Observe safety procedures in Section 7 and 8 during clean up. Spilled product is slippery to walk on. Ventilate the area with fans.

Small Spill: Apply an inert absorbent material on the spill, pick up, and place in a designated waste container. Do not return spilled striper to the original container.

Large Spill: Dike off to prevent sewer entry or ground runoff and reclaim for reuse or disposal. Place only in well vented plastic containers. For remaining residues, if allowed, thoroughly rinse off spill area with water. Otherwise, see Small Spill instructions. The ideal choice for a waste container is an open top dense polyethylene or polypropylene plastic.

Section 7
HANDLING & STORAGE MEASURES

Handling Procedures and Equipment: Wear protective gear (see Section 8). DO NOT use in enclosed space. Open containers slowly to relieve any pressure build up. Keep product out of eyes. Avoid contact with skin. Keep away from food and food products. Keep out of reach of children. Do not smoke when using this product.

Storage Requirements: Protect container against physical damage by storing in a designated, cool, dry, ventilated area away from foodstuffs. Do not store above 100°F (38°C). Store large quantities in buildings designated and protected for storage of combustible liquids.

Section 8
EXPOSURE CONTROL & PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL / STEL	ACGIH TLV / STEL	OTHER
Benzyl Alcohol	N / AV	N / AV	IRR, CBL
Petroleum Distillate, Aromatic	N / AV	N / AV	IRR, CBL
Triethanolamine	N / AV	5 mg / m3	IRR

HMIS III Codes: Health = 1, Flammability = 1, Physical Hazard = 0, Chronic Hazard = No

Engineering Controls: No extra measures are needed if TLV is not exceeded. Use local exhaust ventilation (explosion proof) to keep vapor concentration (TLV) below exposure limits. Maintain a safety shower and eye wash station near the work area.

Personal Protective Equipment: Gloves, respirator, eyewear, footwear, clothing

Respiratory Protection: Use engineering controls to reduce emission levels when spraying. When spraying, use an approved NIOSH respirator of an organic vapor / mist cartridge type.

Protective Clothing: Wear Neoprene® rubber gloves, boots, and apron.

Eye Protection: Wear tight fitting goggles and face shield for material transfer and application.

Section 9
PHYSICAL & CHEMICAL PROPERTIES

Boiling Point: > 100°C

Melting Point: < 0°C

Solubility in Water: Disperses

pH Concentration: 9 to 11

pH (10%): N / AP

Viscosity (Brookfield cPs): 6000 to 15000

Vapor Pressure (mmHg): 9 mmHg 20°C

Coefficient Water / Oil Distribution: < 1

VOC (EPA Method 24): 440 g / L and 67 g / L (alternate)

Appearance / Color / Odor: Off-white viscous emulsion / characteristic odor

Odor Threshold: N / AV

Specific Gravity (Water = 1): 1.01

Vapor Density (Air = 1): > 1

Evaporation Rate (Water = 1): < 1

Section 10

STABILITY & REACTIVITY

Stability:	Stable
Incompatibility (Avoid):	Avoid contact with strong mineral acids, strong oxidizers, or strong alkalis
Reactivity / Conditions:	Avoid hot and cold storage (may cause separation)
Conditions to Avoid:	Do not expose to open flame and sparks
Hazardous Decomposition Products:	High heat may cause decomposition to carbon monoxide, carbon dioxide, or other organic products

Section 11

TOXICOLOGICAL INFORMATION

Acute Exposure Effects:	Vapors and mists are irritating to eyes, skin, and respiratory system. Eye and skin contact produces stinging, itching, watery eyes, and redness. Prolonged skin contact or ingestion may allow absorption of potentially harmful amounts of material, with symptoms of nausea, dizziness, and other gastrointestinal complications.
Chronic Exposure Effects:	Repeated and prolonged contact (over period of a few weeks) may produce dermatitis.
Irritancy of Product:	Moderate
Skin and Respiratory Sensitization:	Not likely to occur
Genetic Toxicity:	This product contains no known ingredients listed by OSHA, ACGIH, IARC, NTP, or Health Canada that are considered carcinogenic, teratogenic, or other known ingredients that would interfere with reproduction.

Section 12

ECOLOGICAL INFORMATION

Biodegradability (40 CFR 796.3100):	Chemical Oxygen demand (COD): N/AV
Aquatic Toxicity (EPA-600-4-002):	Not determined.
Other:	Entry of large quantities of product in waterways may be toxic to marine animals.

Section 13

DISPOSAL CONSIDERATIONS

Waste Disposal Method:	Unusable material should be properly drummed. Liquid wastes are not permitted in landfills. This product is not considered a hazardous waste under RCRA. Unusable liquid may be absorbed on an inert absorbent material, drummed, and taken to a chemical or industrial landfill. In some areas, disposal by incineration or flushing into a sanitary sewer with plenty of water may be permissible. Consult your local, state (provincial), and federal agencies for proper disposal method in your area. Do not contaminate water supply when disposing of wastes or containers.
-------------------------------	--

Section 14

TRANSPORT INFORMATION

Proper Shipping Name:	Not Regulated
TDG / DOT Hazard Class:	N / AP
TDG / DOT ID Number:	N / AP
TDG / DOT Packing Group:	N / AP
TDG / DOT Label / Placard:	N / AP
PIN:	N / AP

Section 15

REGULATORY INFORMATION

WHMIS Classification:	D2B
RCRA Hazardous Waste Nos.:	None
TSCA:	All components of this product are registered under regulations of the Toxic Substances Control Act
RQ CERCLA 40 CFR Part 302:	None
SARA 313 Toxic Chemicals:	None

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations (CPR)*. The MSDS contains all of the information required by the CPR.

Newlook products can be used safely with proper protective equipment and with proper handling practices consistent with label instructions and the MSDS. Before using any product, be sure to read the complete label and the MSDS. As a further word of caution, Newlook advises that serious accidents have resulted from the misuse of "emptied" containers, which retain residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such container to heat flame, sparks, or other sources of ignition; they may explode or develop harmful vapors and possibly cause injury or death. Empty containers must be cleaned by triple rinsing with water or an appropriate solvent. Empty containers must be sent to the drum reconditioner before reuse.

Section 16

OTHER INFORMATION

IMPORTANT: The MSDS should be read before product disposal. Pass MSDS information to all persons who could be exposed to the product. The MSDS has been prepared according to OSHA Hazard Communication Standard (29 CFR 1910.1200). To the best of our knowledge, the information

contained herein is accurate and based on sources believed to be reliable. However, since data, safety standards, and government regulations are subject to change, Newlook International, Inc. makes no warranty, either expressed or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. The data on this sheet is related only to this specific material. It may not be valid for this material if used in combination with any other materials. It is the end user's responsibility to determine suitability and completeness of this information with regards to a particular use. Additional information may be necessary or helpful for specific conditions and circumstances of use. Unknown hazards may exist and this material should be use with caution. Newlook International, Inc. assumes no legal responsibility for use or reliance upon this data.

DISCLAIMER: All statements, technical information, and recommendations contained herein are based on available scientific tests or data, which we believe to be reliable. The accuracy and completeness of such data are not warranted or guaranteed. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. Newlook International, Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of our products, from incompatible product combinations, or from failure to follow instructions, warnings, and advisories in the product label and Material Safety Data Sheet.